

Dong Chau Construction Environment Ltd., Co
16/27A Dinh Tien Hoang Street, Dakao Ward, District 1 Ho Chi Minh city
Tel: +84 8 62702191 Fax: +84 8 39107692
Email: Sales@dongchau.net Web: www.dongchau.net



www.dongchau.net

LIQUID FILTRATION CATALOGUE

Your right choice for perfect filtration





www.dongchau.net

Light Duty Cartridge Vessel- LCF Series

Swing Eye Bolt Closure Design

Versatile design for general purpose application cartridge vessel, available in 3 , 5 and 7 rounds in SS304 and SS316 material. We are able to supply for all industrial standard DOE and SOE configuration of up to 50” length cartridge

Features:

- Convenient Swing Eye Bolt closure design for easy cartridge change out
- Unique design able to fit either DOE (double open end) or SOE with “222” configuration.
- Other SOE configurations ‘226’ also available
- SS304 and SS316 material construction are our standard.
- Smooth Bead blasted finishing for easy cleaning, electro-polishing is optional
- Max Operating pressure – 10 Bar at 25 Deg C
- Inlet/Outlet Connection -1 ½” NPT or 2” -3” ANSI Flange
- Vent/Drain -¼” / ¾” NPT
- O Ring – EPDM, Viton or Telfon encapsulated Viton
- Connection Option -DIN, JIS10K Flange, BSP coupling or others.



Order information:

LCF 520	CS	-10-	020A
#of rounds 3, 5, 7, 9	A- SS304 S- SS316 SL- SS316L	6 bar 10 bar	B- BSP N- NSP A- ASI Flange J- JIS Flange D- DIN Flange Flange size 2”, 3”
Length of Cartridge 10”, 20”, 30”, 40”, 50”			



www.dongchau.net

Light Duty Cartridge Vessel- LCF Series

V Clamp Closure Design

Versatile design for general purpose application cartridge vessel, available in 3 , 5 and 7 rounds in SS304 and SS316 material. We are able to supply for all industrial standard DOE and SOE configuration of up to 50” length cartridge

Features:



- Convenient V Clamp closure design for easy cartridge change out
- Unique design able to fit either DOE (double open end) or SOE with “222” configuration.
- Other SOE configurations ‘226’ also available
- SS304 and SS316 material construction are our standard.
- Smooth Bead blasted finishing for easy cleaning, electro-polishing is optional
- Max Operating pressure – 10 Bar at 25 Deg C
- Inlet/Outlet Connection -1 ½” NPT or 2” -3” ANSI Flange
- Vent/Drain -¼” / ¾” NPT
- O Ring – EPDM, Viton or Telfon encapsulated Viton
- Connection Option -DIN, JIS10K Flange, BSP coupling or others.

Order information:

LCF 520	CS	-10-	020A
#of rounds 3, 5, 7, 9 Length of Cartridge 10”, 20”, 30”, 40”, 50”	A- SS304 S- SS316 SL- SS316L	6 bar 10 bar	B- BSP N- NSP A- ASI Flange J- JIS Flange D- DIN Flange Flange size 2”, 3”