

Dong Chau Construction Environment Ltd., Co  
16/27A Dinh Tien Hoang Street, Dakao Ward, District 1 Ho Chi Minh city  
Tel: +84 8 62702191 Fax: +84 8 39107692  
Email: [Sales@dongchau.net](mailto:Sales@dongchau.net) Web: [www.dongchau.net](http://www.dongchau.net)



[www.dongchau.net](http://www.dongchau.net)

## LIQUID FILTRATION CATALOGUE

Your right choice for perfect filtration





www.dongchau.net

# Stainless Steel Filter Cartridge - USC Series

*For High Temperature, High Pressure application*

**Features:**

- Choice of SS304, SS316, SS316L material
- Depth or Pleated Type Construction
- No Fiber Migration
- Up to 0.2 micron absolute
- Double open end or Single Open end configuration available



**Technical Parameter:**

- Pore Size ( micron )                      0.2, 1, 5, 10, 25, 50, 75, 100 micron
- Material of Construction                  SS304, SS316, SS316L
- Gasket/ O Ring material                  EPDM, Viton, Teflon
- Length    10'' to 40''
- Inner Diameter                                33 mm
- Outer Diameter                                68 mm

**Order information:**

USC	0.2-	10-	3	E
SS Cartridge	Retention Rating 0.2 1 5-100	Cartridge length 10'' 20'' 30'' 40''	End Configuration DOE 3-SOE 222/Flat End 7-SOE 222/Fin End 8-SOE 222/Fine End	Oring material E - EPDM V - Viton T - Teflon